












Product Model	0021056 (CG-2)	0021057 (CG-3)	0021102 (CWC-3)	0021032 (CR-2)	0021033 (CR-4)
Picture					
Operating Current	12mA		2mA	3mA	
Unit Size	84mm x 30mm x 10mm		58mm x 30mm x 12mm	50mm x 40mm x 13mm	
Operating Voltage	1 x 27A -12V battery			1 x 23A -12V battery	
Encoding Chip	SC2262		SCT2260	LX2260A-R4	
Encoding Type	Fixed code by soldering				
Antenna	Telescopic Antenna		Built-in Antenna		
Waterproof	No	No	Yes	Yes	Yes
Working distance with the receiver (with internal antenna)	300M~500M		30M~60M		
Working distance with the receiver (with external antenna)	500M~1000M		50M~100M		

Product Model	0021092 (CWB-1)	0021093 (CWB-2)	0021094 (CWB-3)	0021095 (CWB-4)	0021009 (CS-4)
Picture					
Operating Current	8mA				3mA
Unit Size	56mm x 32mm x 12mm				60mmx25mmx15mm
Operating Voltage	2 x CR2016 -3V button cell batteries				1 x 27A -12V battery
Encoding Chip	PT2260-R4S				LX2260A-R4
Encoding Type	Fixed code by soldering				
Antenna	Built-in Antenna				Telescopic Antenna
Waterproof	Yes				No
Working distance with the receiver (with internal antenna)	30M~60M				80M~110M
Working distance with the receiver (with external antenna)	50M~100M				100M~200M

Product Model	0021000 (C-1)	0021001 (C-2)	0021002 (C-3)	0021003 (C-4)	0021004 (C-3-2)
Picture					
Operating Current	4mA~7mA				
Unit Size	58mm x 39mm x 16mm				
Operating Voltage	1 x 23A -12V battery				
Encoding Chip	PT2264/SC2262/PT2262				
Encoding Type	Fixed code by soldering				
Antenna	Telescopic Antenna				
Waterproof	No				
Working distance with the receiver (with internal antenna)	80M~110M				
Working distance with the receiver (with external antenna)	100M~200M				

Product Model	0021010 (CP-1)	0021011 (CP-2)	0021012 (CP-4)	0021014 (CP-8)	0021016 (CP-15)
Picture					
Operating Current	5mA				
Unit Size	85mm x 36mm x 16mm				100mm x 45mm x 20mm
Operating Voltage	1 x 23A -12V battery				
Encoding Chip	PT2264/SC2262/PT2262				
Encoding Type	Fixed code by soldering				
Antenna	Telescopic Antenna				
Waterproof	No				
Working distance with the receiver (with internal antenna)	300M~500M				
Working distance with the receiver (with external antenna)	500M~1000M				

Product Model	0021017 (CV-2)	0021018 (CV-4)	0021019 (CV-6)	0021020 (CV-8)	0021022 (CV-12)
Picture					
Operating Current	5mA				
Unit Size	110mm x 50mm x 18mm				
Operating Voltage	1 x 23A -12V battery				
Encoding Chip	PT2264/SC2262/PT2262				
Encoding Type	Fixed code by soldering				
Antenna	Telescopic Antenna				
Waterproof	No				
Working distance with the receiver (with internal antenna)	300M~500M				
Working distance with the receiver (with external antenna)	500M~1000M				

Product Model	0021015 (CV-15)	0021050 (CV-2-2)	0021051 (CV-4-2)	0021052 (CV-6-2)	0021072 (CV-8-3)
Picture					
Operating Current	5mA				
Unit Size	110mm x 50mm x 18mm				
Operating Voltage	1 x 23A -12V battery				
Encoding Chip	PT2264/SC2262/PT2262				
Encoding Type	Fixed code by soldering				
Antenna	Telescopic Antenna				
Waterproof	No				
Working distance with the receiver (with internal antenna)	300M~500M				
Working distance with the receiver (with external antenna)	500M~1000M				

Product Model	0021023 (CB-1)	0021024 (CB-2)	0021047 (CB-3-2)	0021026 (CB-4)	0021027 (CB-6)
Picture					
Operating Current	15mA~30mA				
Unit Size	135mm x 42mm x 25mm				
Operating Voltage	1 x 6F22 -9V battery				
Encoding Chip	PT2264/SC2262/PT2262				
Encoding Type	Fixed code by soldering				
Antenna	Telescopic Antenna				
Waterproof	No				
Working distance with the receiver (with internal antenna)	800M~1000M				
Working distance with the receiver (with external antenna)	1000M~2000M				

Product Model	0021028 (CB-8)	0021029 (CB-12)	0021067 (CBW-1)	0021068 (CBW-2)	0021070 (CBW-4)
Picture					
Operating Current	15mA~30mA				
Unit Size	135mm x 42mm x 25mm		100mm x 68mm x 50mm		
Operating Voltage	1 x 6F22 -9V battery				
Encoding Chip	PT2264/SC2262/PT2262				
Encoding Type	Fixed code by soldering				
Antenna	Telescopic Antenna		SMA Telescopic Antenna		
Waterproof	No		Yes		
Working distance with the receiver (with internal antenna)	800M~1000M				
Working distance with the receiver (with external antenna)	1000M~2000M				

Product Model	0021044 (CB-2V)	0021048 (CB-2V-AC)	0021045 (CB-2N)	0021046 (CB-2N-2)
Picture				
Operating Current	15mA~30mA			
Trigger signal mode	Input DC5~28V	Input AC100~240V	Connect two wires	
Unit Size	135mm x 42mm x 25mm	100mm x 68mm x 50mm	135mm x 42mm x 25mm	
Operating Voltage	1 x 6F22 -9V battery			
Encoding Chip	PT2264/SC2262/PT2262			
Encoding Type	Fixed code by soldering			
Antenna	Telescopic Antenna	SMA Telescopic Antenna	Telescopic Antenna	
Waterproof	No	Yes	No	
Working distance with the receiver (with internal antenna)	800M~1000M			
Working distance with the receiver (with external antenna)	1000M~2000M			