# 6" / 150mm DC 12V/24V Mini Pen Type Linear Actuator

### Application:

Mainly used for Robots, Boat, Car, Lifting Platform, Electric Bicycle, Fan, Home Appliance, Automation Equipment etc. It can push, pull, lift and descend other devices.

#### Feature:

High quality

Generate linear motion (extending or retracting)

DC motor drive

Low power consumption

Low noise design

Stainless steel telescopic rod

Wear and corrosion resistance

Overload protection

External stroke limit prevents over-extending and over-compressing.

# Specifications:

Working voltage: DC 12V or DC 24V

Extension: 6"/ 150mm

Compressed length between two mounting holes (shaft retracts completely): 275mm Extended length between two mounting holes (shaft extends completely): 425mm

Speed: 7.5mm±1mm/second or 15mm±2mm/second

Max Load capacity: 25 Pound / 12Kg / 120N at 7mm/second, or 6 Pound / 3Kg / 30N at 15mm/second. The linear actuator can get the maximum load capacity when it operates in the vertical direction.

Working current: (you should use a 3A power adapter to power this actuator.)

	Max Load	Working Current			
Speed		12V version		24V vesion	
		No Load	Full Load	No Load	Full Load
15mm±2mm/second	6 Pound / 3Kg / 30N	0.15A	0.52A	0.08A	0.3A
7.5mm±1mm/second	25 Pound / 12Kg / 120N	0.1A	0.4A	0.05A	0.25A

Outer diameter: 20mm Mounting holes diameter: 5mm

Environment temperature: -26°C to 85°C

Noise level: lower than 40dB

IP rating: IP54 Weight: 220g

## Operation:

Extending or retracting movement.

Moving direction can be changed by switching polarity.

